

# SafetyLink® TileLink™

## Rafter-Mounted Anchor

Quick to install, with amazing performance ability SafetyLink's patented TileLink™ is the perfect anchor for tile and slate roofs.

Its combines energy absorbing capabilities with a design that is practically invisible when looking at the roof.

- Patented energy absorbing anchor.
- Multi-directional 316 stainless steel TileLink for use on tile or roofs.
- Fixes to rafter with five roofing screws.
- Five alternate fixing rows enables the TileLink to be positioned to suit the pattern of the roof tile.
- Fits snugly between the existing tiles eliminating waterproofing issues.
- Fast simple unit for installation, rated as a one person anchor.
- Tested and manufactured to AS/NZS 1891.4 and European BS EN 795:2012, CEN/TS 16415:2013.



**Episode Winner on ABC1 The New Inventors**

**ADJUSTS TO SUIT TILE PATTERN**

**NO NEED TO CUT SARKING THEREFORE ELIMINATING WATERPROOFING ISSUES**

Distributors of SafetyLink Pty Ltd Products [www.heightsafety.com](http://www.heightsafety.com)

**All Trades Abseiling**

Po Box 774 | Newport Beach | 2106

0412 227 578

[matt@alltradesabseiling.com.au](mailto:matt@alltradesabseiling.com.au) | [www.alltradesabseiling.com.au](http://www.alltradesabseiling.com.au)





# SafetyLink® TileLink™

## Rafter-Mounted Anchor

### TileLink Complete Unit

PRODUCT CODE: TILEL001

Quick to install, with amazing performance ability SafetyLink's patented TileLink™ is the perfect anchor for tile and slate roofs.

It combines energy absorbing capabilities with a design that is practically invisible when looking at the roof.

The TileLink's design emulates the extraordinary FrogLinks™ energy absorbing regions, allowing it in the event of a fall to reduce the impact on the structure and person attached to the TileLink™.

Its sleek design means fixing to a rafter is a simple task of screwing five (12 gauge, 50mm roofing screws) through the TileLinks existing holes. Five alternate fixing rows enable the TileLink™ to be positioned to suit the pattern of the roof tile. The TileLink fits snugly between the existing tile eliminating waterproofing issues.

The 316 stainless steel TileLink™ is tested and manufactured in accordance with the applicable Australian and New Zealand Standards AS/NZS 1891.4 and European BS EN 795:2012, CEN/TS 16415:2013 one person anchor.



Distributors of SafetyLink Pty Ltd Products [www.heightsafety.com](http://www.heightsafety.com)

**All Trades Abseiling**

Po Box 774 | Newport Beach | 2106

0412 227 578

[matt@alltradesabseiling.com.au](mailto:matt@alltradesabseiling.com.au) | [www.alltradesabseiling.com.au](http://www.alltradesabseiling.com.au)

